

## **Material Safety Data Sheet**

According to Regulation No 1907/2006/EC - REACH, No. 453/2010 and No 1272/2008/EC - CLP

Version No: 4.1

Date of revision: 01/21/2015 Replaced version No: 4.0

SECTION 1	Identification of the substance/mixture and of the company/undertaking				
1.1	Product identifier  Black and white reversal film set, part A				
	Other name or labeling of product:				
1.2	Relevant identified uses of the substance or mixture and uses advised against				
	Concentrate of developer for processing of Fomapan R100				
1.3	Details of the supplier of the safety data sheet				
	Supplier : Downstream User (Producer Mixture)	FOMA BOHEMIA spol. s r.o.(Ltd.) J. Krušinky 1737/6, 500 02 Hradec Králové tel: 495 733 111			
	E-mail address and phone number	ilona.spackova@foma.cz +420495733368			
1.4	Emergency telephone number (Czech)	Toxicologic institute (TIS) Na Bojišti 1, 128 21 Praha 2 Tel. 224919293, 224915402 (continuous telephone information service)			

SECTION 2	Hazards identification
2.1	Classification (according to Regulation No 1272/2008 – CLP)
	Carc.2;H351 Muta 2;H341 Eye Irrit.2;H319
	Skin Irrit.2;H315 SkinSens.1;H317 Aquatic Acute 1;H400
	Aquatic Chronic2;H411  Classification (according to Directive No 1999/45/ES – (DPD)
	Carc.Cat.3;R40 Muta.Cat.3;R68 Xi;R36/38,R43 N;R50

The most important adverse physicochemical, human health and environmental effects: Upon contact with the eyes can cause serious irritation. Suspected of causing cancer and genetic defects by long term exposure. .May cause an allergic skin reaction. Acute toxicity to aquatic organisms with long lasting effects.

2.2	Label elements (according to Regulation No 1272/2008/EC- CLP)			
Identification of pr	oduct	Black and white reversal film set, part A		
hazard pictogram				
signal word		Warning		
hazard	H351	Suspected of causing cancer		
statement(s) (H-,	H341	Suspected of causing genetic defects		
phrases)	H315	Causes skin irritation.		
	H319	Causes serious eye irritation.		
	H317	May cause an allergic skin reaction		
	H410	Very toxic to aquatic life with long lasting effects		
precautionary	P102	Keep out of reach of children		
statement	P262	Do not get in eyes, on skin, or on clothing.		
(P- phrases)	P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing		
	P308+P313	IF exposed or concerned: Get medical advice/attention.		
	P273	Avoid release to the environment		
	P501	Dispose of contents/container to collecting place for dangerous waste in		
	F301	accordance with national regulations.		
		Contain: hydroquinone, potassium hydroxide		
		Contain. Hydroquillone, potassium hydroxide		
		FOMA BOHEMIA spol. s r.o., J. Krušinky 1737/6, 500 02 Hradec Králové tel: 495 733 111		

2.3	Other hazards
	The substance does not belong to the category of PBT, vPvB, SVHC

SECTION 3	Composition/information on ingredients						
3.2	Mixtures						
Folder name	Registration number	Index number	CAS number	ES number	Content % in the solution	Classification	
Potassium carbonate	01- 2119532646 -36-0000	Not available	584-06-7	209-529-3	< 10	Eye Irrit.2;H319 Skin Irrit.2;H315 STOT SE 3;H335	Xi;R36/37/38

Hydroquinone	01- 2119524016 -51-xxxx	604-005- 00-4	123-31-9	204-617-8	< 5	Carc.2;H351 Muta.2;H341 AcuteTox.4;H302 EyeDam.1;H318 SkinSens.1;H317 Aquatic Acute 1; H400 AquaticChronic1; H410 M(acute)=10, M (chronic)=1	CarcCat3;R40 MutaCat3;R68 Xn;R22 Xi;R41,R43 N;R50
Potassium hydroxide	01- 2119487136 -33	019-002- 00-8	1310-58- 3	215-181-3	< 1	SkinCorr.1A;H314 AcuteTox.4;H302 Met.Corr.1;H290	C;R35 Xn;R22

Solution

(Full text R, H-phrases... section 16)

SECTION 4	First aid measures		
4.1	Description of first aid measures		
	Disabled person to lead from the contaminated area, bringing it into a state of peace and to facilitate breathing by loosening clothing, watch, and if necessary to maintain its vital functions. If you are experiencing symptoms of acute injury (shortness of breath, persistent cough, chest pain, nausea, impaired sensory perception, fainting, etc.), call a physician or transport the injured person to a doctor.		
	After contact with skin: Wash affected area thoroughly with water.		
	Eye Contact: Remove any contact lenses and eye as soon as possible wash with plenty water necessary, open up violence cramped eyelids. Avoid contamination not contaminated eye wa liquid Do not neutralize. Seek medical help.		
	Exposure by inhalation: Remove patient to fresh air, lukewarm water rinse eyes, mouth and nasal cavity.		
	Ingestion: Affected person calm, clear water rinse. Place to drink a glass (about 0.4 dl) of cold water. Do not induce vomiting. If affected persone vomit spontaneously, control to prevent inhalation of vomit. Do not administer activated charcoal, and no neutralizing agent. Call a physician or transport the affected person to a doctor.		
4.2	Most important symptoms and effects, both acute and delayed		
	Not known		
4.3	Indication of any immediate medical attention and special treatment needed		
	In the workplace, running water and soap.		

SECTION 5	Firefighting measures
5.1	Extinguishing media The product (liquid solution) is not flammable. Extinguishing agents adapt burning nearby.
	Inappropriate extinguishing media: N.a.
5.2	Special hazards arising from the substance or mixture
	At elevated temperatures or by contact with acid can release sulphur dioxide

5.3	Advice for firefighters: Breathing apparatus, workwear		
SECTION 6	Accidental release measures		
6.1	Personal precautions, protective equipment and emergency procedures		
	Zoom out persons not participating in the elimination of consequences of the accident out of reach. Ventilate enclosed spaces. When removing the consequences of the accident using the prescribed personal protective equipment. When working on the disposal of the accident contained breathing apparatus and full protective suit. No smoking and treatment with an open fire.		
6.2	Environmental precautions		
	Do not allow substance to enter soil, sewage system, surface and groundwater.		
6.3	Methods and material for containment and cleaning up		

least strongly dilute with water.

Reference to other sections

See section 13

6.4

Let soak it to inert absorption products. Rinse the affected area thoroughly with water. Small leak at

SECTION 7	Handling and storage
7.1	Precautions for safe handling  While working to comply with basic requirements of safe work. Wear recommended personal protective equipment. Avoid contact with eyes.  By manipulation prohibits eating, drinking and smoking, working with hot materials and open flame. Equipment must be equipped with means of extinguishing in enclosed areas, ventilation should be provided, either naturally or forced.  Workplaces must be kept clean and escape routes must remain free.
7.2	Conditions for safe storage, including any incompatibilities  Store in original containers in a cool, dry and well ventilated place. Containers should be stored separately from food. The working solution prepare according to the instructions.
7.3	Specific end use(s) See in 1.2. , Other uses – not available

SECTION 8	Exposure controls/personal protection		
8.1	Control parameters  Government Regulation No 361/2007 Coll Conditions for health workers at work and occupational exposure limits in the air of workplaces and ways of measuring and evaluating. (Czech)  Hydroquinone: PEL 2 mg/m³ NPK-P 4 mg/m³  Potassium hydroxide PEL 1 mg/m³ NPK-P 2 mg/m³  Potasium carbonate PEL 5 mg/m³ NPK-P 10 mg/m³  Substance is not listed in Notice. No.432/2003 Coll., Laying down limit values of biological exposure		
	tests: not available		

	DNEL: (hydroquinone)	Workers	General			
	Long-Term – derm., systemic. effect	128 mg/kg bw/day	64 mg/kg bw̯/day			
	Long-Term – inhal., systemic. effect	7 mg/m <sup>3</sup>	1.74 mg/mౢ <sup>3</sup>			
	Long-Term – inhal., local. effect	1 mg/m <sup>3</sup>	0,5 mg/m <sup>3</sup>			
	PNEC : (hydroquinone)					
	Freshwater	0.114mg/l				
	Seawater	0.0114 mg/l				
	Soil	0.129 ug/kg sedim	ent dw			
	Mikroorganisms in Sewasge Treatment Plant	0.71mg/l				
	DNEL: (potassium hydroxide)	Workers	General			
	Long-Term – inhal., local. effect	1 mg/m³	1 mg/m <sup>3</sup>			
8.2	Exposure controls					
	Individual protection measures, incl. protective equipment					
	Technical measures: Working with a local source of suction and running water for the irrigation needs of the eyes, wash your hands or contaminated parts of the skin.					
	Tightly closed containers and equipment, natural and mechanical ventilation. Do not allow product to the eyes, mouth, inhalation, skin contact. Do not eat, drink or smoke. Avoid contact with food substances and drinks. After work wash hands with soap and water. Alternatively, take off contaminated clothing.					
	Respiratory protection: During normal handling is not required.					
	Hand protection: Use rubber (PE, nitril) gloves					
	Eye protection: Safety glasses					
	Skin protection: Workwear					
	Environmental exposure: Provide preventing spill into waterways, soil and drainage.					

SECTION 9	Physical and chemical properties	
9.1	Information on basic physical and chemical properties	
	Appearance	Moderate yellow liquid
	Odour	Moderate, nonspecific
	рН	cca 10.2-10.5
	Melting point/freezing point	cca 0 ° C
	Initial boiling point and boiling range	cca 100 ° C
	Flash point	Fireproof
	Evaporation rate	N.a.
	Flammability	Incombustible
	Upper/lower flammability or explosive limits	Irrelevant
	Vapour pressure	<20 mbar
	Vapour density	Unknown
	Oxidising properties	No
	Relative density	1.241,25 g/cm <sup>3</sup>

	Solubility – watter	Solution
	Partition coefficient: n-octanol/water	Unknown
	Auto-ignition temperature	Irrelevant
	Decomposition temperature	N.a.
	Viscosity;	N.a.
	Explosive properties	No
9.2	Other information	
	Fat solubility	N.a.
	Conductivity	N.a.

SECTION 10	Stability and reactivity	
10.1	Reactivity	
	Under normal conditions the product is stable	
10.2	Chemical stability	
	Under normal conditions the product is stable	
10.3	Possibility of hazardous reactions	
	Strong minerale acids	
10.4	Conditions to avoid	
	High temperature	
10.5	Incompatible materials	
	Alluminium	
10.6	Hazardous Decomposition Products	
	Possible development of sulfur dioxide at elevated temperatures and reaction with acids	

<b>-</b>			
SECTION 11	Toxicological informations		
11.1 lı	Information on toxicological effects		
Acute toxicit	ty	Based on available data, the criteria for this classification are not match up	
Skin corrosion/irritation		Causes serious skin irritation	
Serious eye damage/eye irritation		Causes serious eye irritation	
Respiratory or skin sensitisation		May cause an allergic skin reaction	
Germ cell mutagenicity		Suspected of causing genetic defects	
Carcinogenicity		Suspected of causing cancer	
Reproductive toxicity		Based on available data, the criteria for this classification are not match up	
Specific target organ toxicity — single exposure		Based on available data, the criteria for this classification are not match up	

Specific target organ toxicity — repeated exposure	Based on available data, the criteria for this classification are not match up		
Aspiration hazard	Based on available data, the criteria for this classification are not match up		
$LDL_o$ oral, human : > 29 mg/kg ( $LD_{50}$ oral rat: > 320 mg/kg (			
LD <sub>50</sub> derm., rat : > 9000 mg/kg (hy	droquinone)		
LD <sub>50</sub> oral rat: > 320mg/kg (pe	otassium hydroxide)		
Likely routes of exposure and symptoms related to the physical, chemical and toxicological characteristics:			
Toxicity oral. (ingestion / swallowing)	Toxicity oral. (ingestion / swallowing):		
Ingestion may cause irritation or burns to the digestive tract. It causes nausea.			
Toxicity inhal. (inhalation):			
The product (solution) is not dangerous.			
Toxicity dermal.			
May cause irritation (redness) of skin			
Eye Contact:			
Causes serious eye irritation			
Immediate, delayed and chronic effects of short and long term exposure: Suspected of causing cancer and genetic defects			

SECTION	Ecological information		
12			
12.1	Toxicity		
	$LC_{50}$ (fish)/96hod: 0,15 mg/l (hydroquinone) $EC_{50}$ (daphnia)/24hod: 0,11 mg/l (hydroquinone) $LC_{50}$ (pipemphales promelas)/96hour: 0,044mg/l (hydroquinone)		
	EC <sub>50</sub> (water algae)/72hod: 0,33 mg/l (hydroquinone)		
	Mixture is higly toxic for aquatic life		
12.2	Persistence and degradability		
	Hydroquinone is considered to be biologically degradable (test OECD 301 C)		
12.3 Bioaccumulative potential			
	It is not expected		
12.4	Mobility in soil		
	N.a., the product is soluble in water		
12.5	Results of PBT and vPvB assessment		
	Not available. Substances are not identified as a PBT or vPvB		
12.6	Other adverse effects		
	WGK = 1		

SECTION	Disposal considerations
13	

13.1	Waste treatment methods	
	Code and type of waste	09 01 01* – aqueous developer solutions
		15 01 10 * - packaging containing residues of hazardous substances
	The recommended method of disposal of the substance/ preparation:	Spilled product let soak up with inert absorbent material and pass the person authorized to remove. Must not be disposed of with household or other waste. Do not wash into sewers.
	The recommended method of disposal of contaminated product packaging:	Emptied containers (after thorough flushing) can be reused, or to defer to container, designated for separate collection (plastics). Possible slight residuals of hydrochinone in the empty, rinsed container, transform into harmless chinone form. (oxidation process)
	Waste legislation	Directive No. 2008/98/ES

SECTION	Transport information
14	

Land transport ADR/RID (cross-border):

Land transport ADIVINID (C1055- border).	1
UN number	3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,N.O.S. (HYDROQUINONE)
Transport hazard class(es)	9
Packing group	III
Labels	9
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Tunel restriction: E
Remarks:	The product is carried in single or combination packagings containing a net quantity per single or inner packaging of 5 l or less and is not subject to any other provisions of ADR provided packaging meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 (according to chapter 3.3 ADR, special provisions 375)

Maritime transport IMDG:

martime transport mibe:		
UN number	3082	
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,N.O.S. (HYDROQUINONE)	
IMDG class(es)	9	
Packing group	III	
EMS number	F-A, S-F	
Segregation	Category A	
Marine pollutant	Yes	
Labels	9	

Remarks:	The product is packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 l or less and is not subject to any other provisions of IMDG Code relevant to marine pollutants provided the packagings meet the general
	provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. (according to Chapter 2.10, paragraph 2.10.2.7)

Air transport ICAO-TI and IATA-DGR:

UN number	3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,N.O.S. (HYDROQUINONE)
ICAO/IATA class(es)	9
Packing group	III
Labels	9
Packing instructions	Passenger aircraft – Packing instruction 964, max. net quantity per package 450 L
	Cargo aircraft - Packing instruction 964 max. net quantity per package 450 L
Remarks	The product is transported in single or combination packagings containing a net quantity per single or inner packaging of 5 I or less and is not subject to any other provisions of the IATA Dangerous Goods Regulations provided and the packagings used meet defined
	standards. (according to part 4.4 , Special provisions A197)

Environmental hazards	Product contains environmentally hazardous substances: (Hydroquinone)
Special precautions for user	Avoid release to the environment

SECTION 15	Regulatory information
15.1	Safety, health and environmental regulations/legislation specific for the substance or mixture  Regulation (EC) No 1907/2006, registration, evaluation, autorisation, restriction chemicals (REACH) Regulation (EC) No 453/2010 Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures Direction No 67/548/EHS (DSD), 1999/45/ES (DPD) Act No. 350/2011 Coll. On chemical substances and mixtures Decree No. 381/2001 Coll. Establishing the Waste Catalogue. Government Regulation No. 361/2007 Coll. On the health conditions of workers at work
	European Agreement concerning the international carriage of dangerous goods (ADR) applicable as from 1. January 2015  IMDG Code, MSC 93/22/Add.2  IATA Dangerous Goods Regulations, 56th Edition
15.2	Chemical safety assessment
	The chemical safety assessment for the product was n made.

SECTION 16	
Abbreviations, symbols	
Carc.2	Carcinogenity (Category 2)
Muta 2	Mutagenity (Category 2)
Eye Dam.1	Serious eye damage (Category 1)
Skin Corr. 1A	Skin corrosion
Skin Irrit.2	Skin irritation ( Category 2)
Skin Sens.1	Skin sensibilisation (Category 1)
Acute Tox.4	Hazardous to the aquatic environment, acute (Category 4)
Eye Irrit.2	Serious eye irritation (Cat. 2)
Aquatic Acute 1	Hazardous to the aquatic environment, acute (Category 1)
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic (Category 1)
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic (Category 2)
STOT SE 3	Specific target organ toxicity – Single exposure ( Category 3)
Carc. cat.3	Carcinigenity (Category 3)
Muta cat.3	Mutagenity (Category 3)
С	caustic
Xn	harmfull
Xi	irritation
N	hazardous to the aquatic environment
CLP	Regulation (ES) č.1272/2008
DPD	Direction (ES) 1999/45/ES
РВТ	Persistent, bioaccumulation, toxic
vPvB	High persistent, high bioaccumulation
SVHC	Substance of very hight concerns
DNEL	Derivated No-Effect Level
PNEC	Prediction No-Effect Concentration

Materials used for the processing of safety data sheet		
	ded by the producter ata Sheets (MSDS) for chemical substances	
R, H-phrases:		
H351	Suspected of causing cancer	
H341	Suspected of causing genetic defects	
H302	Harmful if swallowed	
H319	Causes serious eye irritation	
H317	May cause an allergic skin reaction	
H318	Causes serious eye damage.	
H400	Very toxic to aquatic life	

H335	May cause respiratory irritation.
H315	Causes skin irritation.
H314	Causes severe skin burns and eye damage
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
R40	Limited evidence of a carcinogenic effect
R68	Possible risk of irreversible effects
R36/38	Irritating to eyes and skin.
R36/37/38	Irritating to eyes and skin.
R36	Causes serious eye irritation
R22	Harmful if swallowed
R35	Cause severe burns
R41	Risk of serious damage to eyes
R43	May cause sensitisation by skin contact
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R50	Very toxic to aquatic organisms

## Guidance regarding the training of workers:

Workers coming into contact with hazardous chemicals or products must have access to data which are presented in this MSDS and be familiar with them clearly.

Person transporting hazardous chemicals and preparations must be familiar with guidelines for emergency response in accordance with regulations on hazardous goods within the meaning of ADR / RID.

The information contained in this MSDS are currently valid data and best practices for use and handling of this substance under normal conditions. Any other use or handling of this substance, which is not consistent with those of MSDS, excludes liability for defects, respectively damage, which would otherwise meet the producter, importer or retailer.

## Revised safety data sheet:

## Revision:

version 4.1 – changes in section 1.3 and 2.2– address of supplier, 14- changed information for maritine and air transport